
	108 235 ASSIFIE	DOWN MAR	i-Look II	NG INTE	LOGAN E RFEROME R	LECTRO- TER STU	JDY II.	CS LAB VOLUME -TR-80-	F19	NDB00K 628-77	F/6 OF RE- -C-0203 NL	-ETC(U)	
	0F AD A 106 2 3 5												
						- 14 - 14 - 1						÷,	
	Ş:n≠ <del>T</del>						- ₩!			<b></b>			, ·
					ratingle) is better			7 .					
						**			w line				
										END DATE FILMED OI - 182 DTIC			



AFGL-TR-80-0237

10

DOWN-LOOKING INTERFEROMETER STUDY II

VOLUME II: HANDBOOK OF RESULTS

80

ALEXANDER S. ZACHOR

UTAH STATE UNIVERSITY LOGAN, UTAH 84322

**MARCH 1980** 

SCIENTIFIC REPORT NO. 3



APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

AIR FORCE GEOPHYSICS LABORATORY AIR FORCE SYSTEMS COMMAND UNITED STATES AIR FORCE HANSCOM AFB, MASSACHUSETTS 01731

81 12 08 296

Qualified requestors may obtain additional copies from the Defense Technical Information Center. All others should apply to the National Technical Information Service.

Unclassified
SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
	3. RECIPIENT'S CATALOG NUMBER
AFGL-TR-80-0237 AD-A108 235	
4. TITLE (and Subtitle)	5. TYPE OF REPORT & PERIOD COVERED
DOWN-LOOKING INTERFEROMETER STUDY II	Scientific Report No. 3
VOLUME II: HANDBOOK OF RESULTS	6. PERFORMING ORG. REPORT NUMBER
	<u> </u>
7. AUTHOR(a)	B. CONTRACT OR GRANT NUMBER(s)
Alexander S. Zachor	F19628-77-C-0203
9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
Atmospheric Radiation Consultants, Inc. 59 High Street	62101F
Acton, Massachusetts 01720	767010AB
11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE
Air Force Geophysics Laboratory (OPR)	March 1980
Hanscom AFB, Massachusetts 01731	13. NUMBER OF PAGES
Monitor/Dean F. Kimball/OPR 14. MONITORING AGENCY NAME & ADDRESS(II different from Controlling Office)	15. SECURITY CLASS. (of this report)
Electro-Dynamics Laboratories	Unclassified
Utah State University	
Logan, Utah 84322	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)	<u> </u>
Approved for public release; distribution	unlimited.
Approved for public research, and the second	White deline provide
17. DISTRIBUTION STATEMENT (of the abetract entered in Block 20, if different from	m Report)
18. SUPPLEMENTARY NOTES	
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)	
Atmospheric transmission, interferometer spectromet	ers, spectral correlation
techniques, minor contaminant species detection.	
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)	
1.	
This volume is a handbook of results for the Down-I Study II (AFGL-TR-80-0236). Three pages of data as	
format for each candidate detection band.	e presented


SECURITY CLASSIFICATION OF THE PAGE	(When Date Entered)
,	
	}
Ì	
i e	
t	
1	
}	
1	
1	
	i
İ	
i	
}	
1	
1	
1	
}	
1	

## PREFACE

This handbook of results for the Down-Looking Interferometer Study II is described and summarized in Section 1 of Volume I. Three pages of data are presented for each candidate detection band in a standard format. The following index gives the number of the first page for each band.

Molecule (Transition)	Detection Band (cm <sup>-1</sup> )	Page
с <sub>2</sub> н <sub>4</sub> о <sub>2</sub>	880-1000	3
сн <sub>4</sub> (v <sub>3</sub> )	3000-3025	6
(v <sub>4</sub> )	1295-1310	9
CH31	790-990	12
co(1-0)	2130-2185	15
CO <sub>2</sub> (blue spike)	2375-2400	18
DF	2500-2700	21
	2700-2900	Accession For
	2900-3000	27 NTIS GRAAI
HBr	2450-2650	DTIC TAS [] Unannounced [] Juntification
HC1	2500-2700	33 <sub>By</sub>
	2700-2900	36 Distribution/
	2900-3000	39
HF	3240-3440	42 A
н	2100-2200	45
HNO3 (2 vg)	887.5-902.5	48

Molecule (Transition)	Detection Band (cm <sup>-1</sup> )	Page
NH <sub>3</sub> (ν <sub>2</sub> )	915-970	51
N <sub>2</sub> 0(2 v <sub>1</sub> )	2525-2590	54
(v <sub>3</sub> )	2160-2210	57
(v <sub>1</sub> )	1250-1320	60
$N0_2(v_1 + v_3)$	2850-2935	63
(v <sub>2</sub> )	710-795	66
so <sub>2</sub> (v <sub>1</sub> + v <sub>3</sub> )	2450-2525	69
(v <sub>1</sub> )	1090-1210	72








Table 1 Detection Parameters for  $\mathsf{C_2H_4O_2}$  880-1000 cm  $^{-1}$  region

QUANTITY	SYMBOL, VALUE	UNITS
DETECTION BAND	880-1000	l-no
Approximate wavelength	10.6	E
* NO. OF SPECTRAL ELEMENTS (for $\Delta v$ = 0.80)	M = 150	
BAND PHOTON RADIANCE (scene)	6.00 × 10 <sup>16</sup>	ph/seccm <sup>2</sup> sr
Maximum of contrast $\tau_{\sigma_{\mathbf{Q}}}}}}}}}}$	$CMAX = 8.38 \times 10^{-20}$	cm²/molec
Mean contrast	$\mu' = 5.50 \times 10^{-20}$	cm²/molec
STANDARD DEVIATION OF CONTRAST	$a^2 = 1.69 \times 10^{-20}$	cm²/molec
* Photon flux density on detector		
from scene	$1.4 \times 10^{15}$	phot/seccm <sup>2</sup>
* from internal sources	1.5 × 10 <sup>15</sup>	phot/sec cm <sup>2</sup>
* TOTAL	$J = 2.9 \times 10^{15}$	phot/sec cm <sup>2</sup>
* BLIP Dx	$4.2 \times 10^{11}$	cm /Hz/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE m	min t <sub>d</sub> = 6.54 × 10 <sup>-4</sup>	Sec
* CORRESPONDING BASELINE NESR	$(NESR)_0 = 2.5 \times 10^{-7}$	W/cm <sup>2</sup> sr cm <sup>-1</sup>
* MINIMUM DETECTABLE QUANTITY D (see figure) "	min $0 = 2.0 - 7.0 \times 10^{12}$	$(molec/cm^2)(W/cm^2 srcm^{-1})$
G M - >tm - xtm -	107 7	(mc) ac/cm <sup>2</sup> ) (W/cm <sup>2</sup> er cm <sup>-1</sup>
















Table 2 Detection Parameters for  $\mathrm{CH}_{l_{\mathrm{L}}}$   $\mathrm{v}_{\mathrm{J}}$  band

Approximate wavelength	QUANTITY	SYMBOL, VALUE	UNITS
3.3 $M = 250$ $CMAX = 1.14 \times 10^{-20}$ $u' = 1.84 \times 10^{-21}$ $a' = 2.71 \times 10^{-21}$ $a' = 2.71 \times 10^{-11}$ $J = 2.1 \times 10^{11}$ $J = 2.1 \times 10^{13}$ $min \ t_d = 7.79$	DETECTION BAND	3000-3025	cm l-
$\begin{array}{llllllllllllllllllllllllllllllllllll$	Approximate wavelength	3.3	E
$ \begin{array}{llllllllllllllllllllllllllllllllllll$		. M = 250	
$c_{MAX} = 1.14 \times 10^{-20}$ $c_{L}' = 1.84 \times 10^{-21}$ $c_{C} = 2.71 \times 10^{-21}$ $c_{C} = 2.71 \times 10^{-10}$ $c_{C} = 2.71 \times 10^{10}$ $c_{C} = 2.5 - 8.0 \times 10^{10}$ $c_{C} = 1.6 \times 10^{10}$	BAND PHOTON RADIANCE (scene)	$2.57 \times 10^{12}$	ph/seccm <sup>2</sup> sr
$ \begin{array}{llll}  & \mu' = 1.84 \times 10^{-21} \\  & \sigma' = 2.71 \times 10^{-21} \\  & \sigma' = 2.71 \times 10^{-21} \\  & \vdots	Maximum of contrast $ au_{V}^{A}$	. $CMAX = 1.14 \times 10^{-20}$	cm <sup>2</sup> /molec
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Mean contrast	$\mu' = 1.84 \times 10^{-21}$	cm <sup>2</sup> /molec
5.9 × 10 <sup>10</sup> 1.5 × 10 <sup>11</sup> 1.5 × 10 <sup>11</sup> 1.3 × 10 <sup>13</sup> 1.3 × 10 <sup>13</sup> 1.3 × 10 <sup>10</sup> 1.3 × 10 <sup>10</sup> 1.3 × 10 <sup>10</sup> 1.3 × 10 <sup>10</sup> 1.5 × 10 <sup>10</sup> 1.6 × 10 <sup>10</sup> 1.7 × 10 <sup>10</sup>	STANDARD DEVIATION OF CONTRAST	$\sigma = 2.71 \times 10^{-21}$	cm²/molec
5.9 × 10 <sup>10</sup> $J = 2.1 \times 10^{11}$ $J = 2.1 \times 10^{11}$ $J = 2.7 \times 10^{10}$ $J = 2.7 \times 10^{10}$ $J = 2.7 \times 10^{10}$ $J = 2.5 \times 10^{10}$ $J = 2.5 \times 10^{10}$	* Photon flux density on detector	1	
1.5 × 10 <sup>11</sup> 1.5 × 10 <sup>11</sup> 1.3 × 10 <sup>13</sup> 1.5 × 10 <sup>10</sup> 1.6 × 10 <sup>10</sup> 1.5 × 10 <sup>10</sup>	* from scene	. 5.9 × 10 <sup>10</sup>	phot/sec cm <sup>2</sup>
$J = 2.1 \times 10^{11}$ $I.3 \times 10^{13}$ $I.6 \times 10^{10}$ $I.6 \times 10^{10}$		. 1.5 × 10 <sup>11</sup>	phot/sec cm <sup>2</sup>
min $t_d = 7.79$ (NESR) $_0 = 6.0 \times 10^{-10}$ min $_0 = 2.5 - 8.0 \times 10^{10}$ $_{0p} = 1.6 \times 10^{10}$		$3 = 2.1 \times 10^{11}$	phot/sec cm <sup>2</sup>
min $t_d = 7.79$ (NESR) $_0 = 6.0 \times 10^{-10}$ min $_0 = 2.5 - 8.0 \times 10^{10}$ $_{0_D}$ = 1.6 × $_{10}$ 10	* BLIP D*	. 1.3 × 10 <sup>13</sup>	cm /Hz/W
(NESR) $_{0} = 6.0 \times 10^{-10}$ min $_{0} = 2.5 - 8.0 \times 10^{10}$ $\sigma_{D}$ = 1.6 × 10 <sup>10</sup>	P PERFORMANCE	. min t <sub>d</sub> = 7.79	sec
min $0 = 2.5 - 8.0 \times 10^{10}$ $\sigma_{D}$ = $1.6 \times 10^{10}$	•	$(NESR)_0 = 6.0 \times 10^{-10}$	W/cm <sup>2</sup> sr cm <sup>-1</sup>
$\sigma_{\rm D}$ = 1.6 × 10 $^{10}$	•	. min $0 = 2.5 - 8.0 \times 10^{10}$	(molec/cm <sup>2</sup> ) (W/cm <sup>2</sup> sr cm <sup>-1</sup> )
	* UNCERTAINTY IN D	· σ <sub>0</sub> ·=1.6×10 <sup>10</sup>	(molec/cm <sup>2</sup> ) (W/cm <sup>2</sup> sr cm <sup>-1</sup> )













Table 4 Detection Parameters for  ${
m CH_3}1$  790-990 cm  $^{-1}$  region

QUANTITY	SYMBOL, VALUE	UNITS
DETECTION BAND	790-990	- J
Approximate wavelength	11.2	Ę
* NO. OF SPECTRAL ELEMENTS (for $\Delta v$ = 0.10)	M = 2000	
BAND PHOTON RADIANCE (scene)	1.14 × 10 <sup>17</sup>	ph/seccm <sup>2</sup> sr
Maximum of contrast $\tau_{\nu}{}^{\alpha}{}_{g_{\nu}}$	CMAX = $3.62 \times 10^{-20}$	cm <sup>2</sup> /molec
Mean contrast	$\mu' = 4.82 \times 10^{-21}$	cm <sup>2</sup> /molec
STANDARD DEVIATION OF CONTRAST	$\sigma' = 4.40 \times 10^{-21}$	cm <sup>2</sup> /molec
* Photon flux density on detector	1	
* from scene	2.6 × 10 <sup>15</sup>	phot/sec cm <sup>2</sup>
* from internal sources	2.7 × 10 <sup>15</sup>	phot/sec cm <sup>2</sup>
* TOTAL	J = 5.3 × 10 <sup>15</sup>	phot/sec cm <sup>2</sup>
* BLIP DX	2.9 × 10 <sup>11</sup>	cm /Hz/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE	min $t_d = 3.63 \times 10^{-3}$	sec
* CORRESPONDING BASELINE NESR	$(NESR)_0 = 1.23 \times 10^{-6}$	W/cm²srcm²l
* MINIMUM DETECTABLE QUANTITY D (see figure) .	min D = 1.0 - 3.5 $\times$ 10 <sup>13</sup>	$(molec/cm^2)(W/cm^2 sr cm^{-1})$
* UNCERTAINTY IN 0	$\sigma_{D'} = 5.96 \times 10^{12}$	$(molec/cm^2)(W/cm^2 sr cm^{-1})$









Table 5 Detection Parameters for CO 1-0 band

SYMBOL	SYMBOL, VALUE	UNITS
DETECTION BAND	2130-2185	cm -1
Approximate wavelength	4.7	Ę
rs (for av = 0.10)	M = 550	¢
ene)	3.66 × 10 <sup>14</sup>	ph/sec cm <sup>2</sup> sr
• • • • • • • • • • • • • • • • • • • •	$CMAX = 2.01 \times 10^{-19}$	cm <sup>2</sup> /molec
	$\mu^{\prime} = 2.09 \times 10^{-20}$	cm <sup>2</sup> /molec
OF CONTRAST	$\sigma' = 3.64 \times 10^{-20}$	cm²/molec
+ bhatan flux density on detector		
	8.3 × 10 <sup>12</sup>	phot/sec cm
* from internal sources	1.0 × 10 <sup>13</sup>	phot/sec cm <sup>2</sup>
	$J = 1.9 \times 10^{13}$	phot/seccm <sup>2</sup>
* BLIP 0,	1.9 × 10 <sup>12</sup>	cm /Hz/W
CAN TIME FOR BL	min t <sub>d</sub> = 0.833	, ec.
* CORRESPONDING BASELINE MESR	$(3)_0 = 1.2 \times 10^{-8}$	W/cm <sup>2</sup> sr cm <sup>-1</sup>
* MINIMUM DETECTABLE QUANTITY D (see figure) min D = $3.0-8.5 \times 10^{10}$	$0 = 3.0 - 8.5 \times 10^{10}$	(molec/cm <sup>2</sup> ) (W/cm <sup>2</sup> sr cm <sup>-1</sup> )
* UNCERTAINTY IN D	$\sigma_{\rm D}$ = 1.8 × 10 <sup>10</sup>	(molec/cm <sup>-</sup> )(W/cm <sup>-</sup> srcm )










Table 6 Detection Parameters for  ${
m CO}_2$  2375-2400 cm $^{-1}$  region

QUANTITY	SYMBOL, VALUE	UNITS
DETECTION BAND	2375-2400	cm. 1
Approximate wavelength	4.19	En
* NO. OF SPECTRAL ELEMENTS (for Av = 0.10)	. м = 250	
BAND PHOTON RADIANCE (scene)	$2.75 \times 10^{13}$	ph/sec cm <sup>2</sup> sr
Maximum of contrast todgo	. $CMAX = **2.71 \times 10^{-20}$	cm <sup>2</sup> /molec
Mean contrast	$\mu' = *9.72 \times 10^{-22}$	cm <sup>2</sup> /molec
STANDARD DEVIATION OF CONTRAST	$\sigma' = **_4.80 \times 10^{-21}$	cm <sup>2</sup> /molec
* Photon flux density on detector	ı	
* from scene	6.3 × 10 <sup>11</sup>	phot/sec cm <sup>2</sup>
* from internal sources	1.9 × 10 <sup>12</sup>	phot/sec cm <sup>2</sup>
* TOTAL	$J = 2.5 \times 10^{12}$	phot/seccm <sup>2</sup>
* BLIP D*	$4.7 \times 10^{12}$	cm /Hz/V
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE	min t <sub>d</sub> = 2.24	sec
	$(NESR)_0 = 3.1 \times 10^{-9}$	W/cm <sup>2</sup> sr cm <sup>-1</sup>
re)	min D = **1.0-2.5 x 10 <sup>11</sup>	(molec/cm <sup>2</sup> ) (W/cm <sup>2</sup> sr cm <sup>-1</sup> )
* UNCERTAINTY IN D	. ° <sub>0</sub> ′ = **5.7 × 10 <sup>10</sup>	$(molec/cm^2)(W/cm^2srcm^{-1})$

Assumes  $CO_2$  temperature =  $850^{\circ}$ K.










Table 7 Detection Parameters for DF  $2500-2700~{
m cm}^{-1}$  region

QUANTITY	SYMBOL, VALUE	UNITS
DETECTION BAND	2500-2700	-1 cm
Approximate wavelength	3.85	wa
* NO. OF SPECTRAL ELEMENTS (for $\Delta v$ = 0.10)	. M = 2000	
BAND PHOTON RADIANCE (scene)	2.81 × 10 <sup>14</sup>	ph/sec cm <sup>2</sup> sr
Maximum of contrast Tudon	$CMAX = 2.62 \times 10^{-19}$	cm²/molec
Mean contrast	$\mu' = 2.86 \times 10^{-22}$	cm²/molec
STANDARD DEVIATION OF CONTRAST	$\sigma' = 6.38 \times 10^{-21}$	cm²/molec
* Photon flux density on detector	ì	
* from scene	$6.4 \times 10^{12}$	phot/sec cm <sup>2</sup>
* from internal sources	$6.8 \times 10^{12}$	$phot/seccm^2$
* TOTAL	, J= 1.3 × 10 <sup>13</sup>	phot/sec cm <sup>2</sup>
* BLIP 0,	. 1.9 × 10 <sup>12</sup>	cm √Hz/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE	min t <sub>d</sub> = 1.02	295
SR	$(NESR)_0 = 1.1 \times 10^{-8}$ re) min D = 0.8 - 2.3 × 10 <sup>11</sup>	W/cm <sup>2</sup> sr cm <sup>-1</sup> (molec/cm <sup>2</sup> ) (W/cm <sup>2</sup> sr cm <sup>-1</sup> )
* UNCERTAINTY IN D	$\sigma_{0'} = 5.6 \times 10^{10}$	(molec/cm <sup>£</sup> )(W/cm <sup>£</sup> srcm <sup>-1</sup> )









Table 8 Detection Parameters for DF  $2700-2900 \text{ cm}^{-1}$  region

QUANTITY	SYMBOL, VALUE	UNITS
DETECTION BAND	2700-2900	-1 cm
Approximate wavelength	3.57	<b>L</b> I
* NO. OF SPECTRAL ELEMENTS (for $\Delta v$ = 0.10)	M = 2000	
BAND PHOTON RADIANCE (scene)	$1.23 \times 10^{14}$	ph/seccm <sup>2</sup> sr
Maximum of contrast $ au_{v}{}_{qv}$	$CMAX = 1.66 \times 10^{-18}$	cm <sup>2</sup> /molec
Mean contrast	$\mu' = 1.45 \times 10^{-20}$	cm <sup>2</sup> /molec
STANDARD DEVIATION OF CONTRAST	$\sigma^* = 9.39 \times 10^{-20}$	cm <sup>2</sup> /molec
* Photon flux density on detector		
* from scene	2.8 × 10 <sup>12</sup>	phot/sec cm <sup>2</sup>
* from internal sources	$3.0 \times 10^{12}$	phot/sec cm <sup>2</sup>
* TOTAL	$J = 5.8 \times 10^{12}$	phot/sec cm <sup>2</sup>
* BLIP DA	2.7 × 10 <sup>12</sup>	cm /Hz/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE	min t <sub>d</sub> = 1.53	sec
* CORRESPONDING BASELINE NESR	$(NESR)_0 = 6.6 \times 10^{-9}$	W/cm²srcm²ì
* MINIMUM DETECTABLE QUANTITY D (see figure)	TY D (see figure) min D = 3.0 - 9.0 $\times$ 10 <sup>9</sup>	(molec/cm2)(W/cm2 sr cm-1)
* UNCERTAINTY IN D	$\sigma_0 = 2.2 \times 10^9$	$(molec/cm^2)(W/cm^2 sr cm^{-1})$
	•	










Table 9 Detection Parameters for DF 2900-3000 cm<sup>-1</sup> region

QUANTITY	SYMBOL, VALUE	UNITS
DETECTION BAND	2900-3000	- l - cm
Approximate wavelength	3.39	E J
* NO. OF SPECTRAL ELEMENTS (for $\Delta v$ = 0.10)	0001 = M	
BAND PHOTON RADIANCE (scene)	$2.56 \times 10^{13}$	ph/seccm <sup>2</sup> sr
Maximum of contrast $\tau_{\alpha g_{\nu}}$	$CMAX = 2.39 \times 10^{-19}$	cm <sup>2</sup> /molec
Mean contrast	$u = 4.34 \times 10^{-21}$	cm²/molec
STANDARD DEVIATION OF CONTRAST	$\sigma = 1.80 \times 10^{-20}$	cm²/molec
* Photon flux density on detector		
* from scene	5.8 × 10 <sup>11</sup>	phot/sec cm <sup>2</sup>
* from internal sources	8.0 × 10 <sup>11</sup>	phot/sec cm <sup>2</sup>
* TOTAL	$J = 1.4 \times 10^{12}$	phot/sec cm <sup>2</sup>
* BLIP D.*	5.2 × 10 <sup>12</sup>	cm /Hz/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE	min t <sub>d</sub> = 3.09	sec
* CORRESPONDING BASELINE NESR	$(NESR)_0 = 2.4 \times 10^{-9}$	W/cm <sup>2</sup> sr cm <sup>-1</sup>
* MINIMUM DETECTABLE QUANTITY D (see figure) .	min D = $1.0 - 2.3 \times 10^{10}$	$(molec/cm^2)(W/cm^2 sr cm^{-1})$
* UNCERTAINTY IN D	$0. \times 8.5 = 5.8 \times 10^9$	(molec/cm2)(W/cm2 sr cm-1)









Table 10 Detection Parameters for HBr  $2450-2650~\mathrm{cm}^{-1}$  region

QUANTITY	SYMBOL, VALUE	UNITS
DETECTION BAND	2450-2650	- J
Approximate wavelength	3.9	Ea
* NO. OF SPECTRAL ELEMENTS (for AV = 0.10)	M = 2000	
BAND PHOTON RADIANCE (scene)	3.39 × 10 <sup>14</sup>	ph/sec cm <sup>2</sup> sr
Maximum of contrast tydy	$CMAX = 2.48 \times 10^{-19}$	cm <sup>2</sup> /molec
Mean contrast	$\mu' = 4.19 \times 10^{-21}$	cm <sup>2</sup> /molec
STANDARD DEVIATION OF CONTRAST	$\sigma' = 2.10 \times 10^{-20}$	cm <sup>2</sup> /molec
* Photon flux density on detector		
* from scene	7.7 × 10 <sup>12</sup>	phot/sec cm <sup>2</sup>
* from internal sources	8.2 × 10 <sup>12</sup>	phot/sec cm <sup>2</sup>
* TOTAL	$J = 1.6 \times 10^{13}$	phot/sec cm <sup>2</sup>
* BLIP D*	1.8 × 10 <sup>12</sup>	cm /Hz/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE	min t <sub>d</sub> = 0.930	Sec
* CORRESPONDING BASELINE NESR	$(NESR)_0 = 1.3 \times 10^{-8}$	W/cm <sup>2</sup> sr cm <sup>-1</sup>
* MINIMUM DETECTABLE QUANTITY D (see figure)	. min D = $3.0 - 8.0 \times 10^{10}$	$(molec/cm^2)(W/cm^2 sr cm^{-1})$
* UNCERTAINTY IN D	$\sigma_0 = 1.9 \times 10^{10}$	$(molec/cm^2)(W/cm^2 sr cm^{-1})$









Table 11 Detection Parameters for HCl  $2500-2700~{
m cm}^{-1}$  region

	SYMBOL, VALUE	UNITS
GUANITITY STAND	2500-2700	cm -1
Approximate wavelength	3.85	พา
* NO. OF SPECTRAL ELEMENTS (for $\Delta v = 0.10$ )	M = 2000	2
BAND PHOTON RADIANCE (scene)	2.81 × 10 <sup>14</sup>	ph/sec cm si
Maximum of contrast $ au_{oldsymbol{arphi}}^{oldsymbol{lpha}}$	$CMAX = 7.11 \times 10^{-2}$	cm /molec
Mean contrast	$u' = 1.16 \times 10^{-21}$	cm <sup>2</sup> /molec
STANDARD DEVIATION OF CONTRAST		
* Photon flux density on detector	2	2
* from scene	6.4 × 10' <sup>2</sup>	phot/sec cm
* from internal sources	6.8 × 10 <sup>2</sup>	phot/sec.cm
* TOTAL	$J = 1.3 \times 10^{13}$	phot/sec ciii
* BLIP D	1.9 × 6.1	
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE	min t <sub>d</sub> = 1.02	sec
* CORRESPONDING BASELINE NESR	$(NESR)_0 = 1.1 \times 10^{-3}$	(molec/rm <sup>2</sup> ) (W/cm <sup>2</sup> sr cm <sup>-1</sup> )
* MINIMUM DETECTABLE QUANTITY D (see figure)	. min D = 3.0 - 9.0 × 10	(molec/cm <sup>2</sup> ) (W/cm <sup>2</sup> sr cm <sup>-1</sup> )
* UNCERTAINTY IN D	σ <sub>0</sub> , = 2.5 × 10	










Table 12 Detection Parameters for HCl 2700-2900 cm region

QUANTITY	SYMBOL, VALUE	UNITS
DETECTION BAND	2700-2900	cm -1
Approximate wavelength	3.57	wi
* NO. OF SPECTRAL ELEMENTS (for $\Delta v$ = 0.10)	M = 2000	
BAND PHOTON RADIANCE (scene)	1.23 × 10 <sup>14</sup>	ph/sec cm <sup>2</sup> sr
Maximum of contrast $\tau_{\nu}^{\alpha}$ g $_{\nu}$	$CMAX = 1.30 \times 10^{-18}$	cm²/molec
Mean contrast	$\mu' = 9.28 \times 10^{-21}$	cm <sup>2</sup> /molec
STANDARD DEVIATION OF CONTRAST	$\sigma' = 6.77 \times 10^{-20}$	cm <sup>2</sup> /molec
* Photon flux density on detector		
* from scene	$2.8 \times 10^{12}$	phot/sec cm <sup>2</sup>
* from internal sources	$3.0 \times 10^{12}$	phot/sec cm <sup>2</sup>
* TOTAL	$J = 5.8 \times 10^{12}$	phot/sec cm <sup>2</sup>
* BLIP D*	$2.7 \times 10^{12}$	cm /Hz/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE m	min t <sub>d</sub> = 1.53	sec
* CORRESPONDING BASELINE NESR	$(NESR)_0 = 6.6 \times 10^{-9}$	W/cm <sup>2</sup> sr cm <sup>-1</sup>
* MINIMUM DETECTABLE QUANTITY D (see figure) min D = 0.5 - 1.25 $\times$ 10 $^{10}$	min $0 = 0.5 - 1.25 \times 10^{10}$	$(molec/cm^2)(W/cm^2 sr cm^{-1})$
* UNCERTAINTY IN D $\sigma_{D^-}$ = 3.1 × 10 $^9$	$\sigma_{D} = 3.1 \times 10^{9}$	(molec/cm <sup>2</sup> ) (W/cm <sup>2</sup> sr cm <sup>-1</sup> )









Table 13 Detection Parameters for HC1 2900-3000 cm<sup>-1</sup> region

DETECTION BAND	STABOL, WALGE	
	2900-3000	- n
Approximate wavelength	3.39	En
* NO. OF SPECTRAL ELEMENTS (for AV = 0.10)	# *	
BAND PHOTON RADIANCE (scene)	2.56 × 10 <sup>13</sup>	ph/sec cm <sup>2</sup> sr
Maximum of contrast $t_{ij} \alpha_{ij}$	$CMAX = 1.64 \times 10^{-18}$	cm²/molec
Mean contrast	$$ $u' = 1.64 \times 10^{-20}$	cm <sup>2</sup> /molec
STANDARD DEVIATION OF CONTRAST	$\sigma' = 9.81 \times 10^{-20}$	cm²/molec
* Photon flux density on detector		
* from scene	5.8 × 10 <sup>11</sup>	phot/sec cm <sup>2</sup>
	8.0 × 10 <sup>11</sup>	phot/seccm <sup>2</sup>
* T0TAL	$3 = 1.4 \times 10^{12}$	phot/sec cm <sup>2</sup>
* BLIP D*	5.2 × 10 <sup>12</sup>	cm VHZ/W
* MINIMIN SCAN TIME FOR BLIP PERFORMANCE .	min t <sub>3</sub> = 3.09	Sec
# CORPERSONDING BASELINE NESR	•	W/cm <sup>2</sup> sr cm <sup>-1</sup>
* MINIMUM DETECTABLE QUANTITY D (see figure) min D = $2.0 - 4.5 \times 10^9$	e) min D = 2.0 - 4.5 × 10 <sup>9</sup>	(molec/cm <sup>2</sup> ) (W/cm <sup>2</sup> sr cm <sup>-1</sup> )
* UNCERTAINTY IN D	$\sigma_0 \sim 1.1 \times 10^9$	(molec/cm <sup>2</sup> ) (W/cm <sup>2</sup> sr cm <sup>-1</sup> )



HF 3240-3440 cm<sup>-1</sup> region





Table 14 Detection Parameters for HF 3240-3440 cm<sup>-1</sup> region

QUANTITY	SYMBOL, VALUE	
DETECTION BAND	3240-3440	cm <sup>-</sup> 1
Approximate wavelength	3.0	<b>w</b> n
* NO. OF SPECTRAL ELEMENTS (for $\Delta v$ = 0.10)	M = 2000	
BAND PHOTON RADIANCE (scene)	5.46 × 10 <sup>12</sup>	ph/seccm <sup>2</sup> sr
Maximum of contrast $\tau_{\nu}\alpha_{g\nu}$	$CMAX = 9.62 \times 10^{-23}$	cm <sup>2</sup> /molec
Mean contrast	$\mu' = 5.70 \times 10^{-26}$	cm <sup>2</sup> /molec
STANDARD DEVIATION OF CONTRAST	$\sigma' = 1.72 \times 10^{-24}$	cm <sup>2</sup> /molec
* Photon flux density on detector		
from scene	1.2 × 10 <sup>11</sup>	phot/sec cm <sup>2</sup>
from internal sources	$3.2 \times 10^{11}$	phot/sec cm <sup>2</sup>
* T0TAL	$J = 4.5 \times 10^{11}$	phot/sec cm <sup>2</sup>
* BLIP D*	8.0 × 10 <sup>12</sup>	cm /Hz/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE	min t <sub>d</sub> = 5.52	Sec
* CORRESPONDING BASELINE NESR	$(NESR)_0 = 1.2 \times 10^{-9}$	W/cm2 sr cm-1
* MINIMUM DETECTABLE QUANTITY D (see figure)	. min $D = 3.0 - 9.0 \times 10^{13}$	$(molec/cm^2)(W/cm^2 srcm^{-1})$
* UNCERTAINTY IN D	$a = 2.1 \times 10^{13}$	(molec/cm <sup>2</sup> ) (W/cm <sup>2</sup> sr cm <sup>-1</sup> )



HI 2100-2200 cm<sup>-1</sup> region





Table 15 Detection Parameters for HI 2100-2200 cm region

QUANTITY	SYMBOL, VALUE	UNITS
DETECTION BAND	2100-2200	r_ u
Approximate wavelength	4.65	Ę
* NO. OF SPECTRAL ELEMENTS (for AV = 0.10)	M = 1000	
BAND PHOTON RADIANCE (scene)	6.19 × 10 <sup>14</sup>	ph/seccm <sup>2</sup> sr
Maximum of contrast $\tau_{\nu}^{\alpha}$ q $_{\nu}$	$CMAX = 2.13 \times 10^{-21}$	cm <sup>2</sup> /molec
Mean contrast	$\mu' = 1.17 \times 10^{-23}$	cm <sup>2</sup> /molec
STANDARD DEVIATION OF CONTRAST	$\sigma' = 9.51 \times 10^{-23}$	cm <sup>2</sup> /molec
* Photon flux density on detector	,	
* from scene	1.4 × 10 <sup>13</sup>	phot/sec cm <sup>2</sup>
* from internal sources	$2.0 \times 10^{13}$	$phot/seccm^2$
* TOTAL	$J = 3.4 \times 10^{13}$	phot/sec cm <sup>2</sup>
* BLIP D*	1.4 × 10 <sup>12</sup>	cm /Hz/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE	min t <sub>d</sub> = 0.629	Sec
* CORRESPONDING BASELINE NESR	$(NESR)_0 = 1.9 \times 10^{-8}$	W/cm <sup>2</sup> sr cm <sup>-1</sup>
* MINIMUM DETECTABLE QUANTITY D (see figure)	min $0 = 1.5 - 3.5 \times 10^{13}$	$(molec/cm^2)(W/cm^2 sr cm^{-1})$
* UNCERTAINTY IN D	$\sigma_{\rm D}$ = 8.9 × 10 <sup>12</sup>	$(molec/cm^2)(W/cm^2 sr cm^{-1})$



HNO<sub>3</sub> 2 v<sub>9</sub> band





Table 16 Detection Parameters for HNO $_3$   $2 v_9$  band

QUANTITY	SYMBOL, VALUE	UNITS
DETECTION BAND	. 887.5-902.5	cm <sup>-</sup> 1
Approximate wavelength	11.2	<b>G</b> I
* NO. OF SPECTRAL ELEMENTS (for $\Delta v = 0.10$ )	. M = 150	
BAND PHOTON RADIANCE (scene)	8.61 × 10 <sup>15</sup>	ph/sec cm <sup>2</sup> sr
Maximum of contrast $\tau_{\alpha}\alpha_{\alpha}$	0.00000000000000000000000000000000000	cm²/molec
Mean contrast	$\mu' = 5.38 \times 10^{-20}$	cm <sup>2</sup> /molec
STANDARD DEVIATION OF CONTRAST	$6.98 \times 10^{-20}$	cm²/molec
* Photon flux density on detector	1	
* from scene	2.0 × 10 <sup>14</sup>	phot/sec cm <sup>2</sup>
* from internal sources	2.1 × 10 <sup>14</sup>	phot/sec cm <sup>2</sup>
* TOTAL	$J = 4.1 \times 10^{14}$	phot/seccm <sup>2</sup>
* BLIP D*	1.2 × 10 <sup>12</sup>	cm MZ/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE	min $t_d = 1.82 \times 10^{-2}$	sec
	$(NESR)_0 = 1.4 \times 10^{-7}$	W/cm <sup>2</sup> sr cm <sup>-</sup>
* MINIMUM DETECTABLE QUANTITY D (see figure)	ITY D (see figure) min D = 3.0 - 8.0 $\times$ 10 <sup>11</sup>	(molec/cm <sup>2</sup> ) (W/cm <sup>2</sup> sr cm ')
* UNCERTAINTY IN D	$\sigma_0 = 1.8 \times 10^{-1}$	(molec/cm <sup>-</sup> /(W/cm srcm /









Table 17 Detection Parameters for NH  $_3$   $^{\rm V}_2$  band

	זוחטר, יחבטר	SILIS
DETECTION BAND	915-970	-1 cm
Approximate wavelength	10.7	wn
* NO. OF SPECTRAL ELEMENTS (for $\Delta v = 0.10$ ) M =	M = 550	
BAND PHOTON RADIANCE (scene)	2.75 × 10 <sup>16</sup>	ph/sec cm <sup>2</sup> sr
Maximum of contrast $ au_{\alpha q_0}$ CMAX =	$CMAX = 9.90 \times 10^{-19}$	cm <sup>2</sup> /molec
	$\mu^{-} = 6.78 \times 10^{-20}$	cm <sup>2</sup> /molec
STANDARD DEVIATION OF CONTRAST	$a^2 = 1.30 \times 10^{-19}$	cm²/molec
* Photon flux density on detector		
* from scene	6.3 × 10 14	phot/sec cm <sup>2</sup>
* from internal sources	$6.9 \times 10^{14}$	phot/sec cm <sup>2</sup>
* TOTAL	$J = 1.3 \times 10^{15}$	phot/sec cm <sup>2</sup>
* BLIP D.*	6.2 × 10 <sup>11</sup>	cm /Hz/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE min td "	min $t_d = 7.46 \times 10^{-3}$	Sec
* CORRESPONDING BASELINE NESR	(NESR) $_0 = 4.1 \times 10^{-7}$	W/cm <sup>2</sup> sr cm <sup>-1</sup>
* MINIMUM DETECTABLE QUANTITY D (see figure) min D =	. min D = 4.5 - 7.3 × 10 <sup>11</sup>	(molec/cm <sup>2</sup> ) (W/cm <sup>2</sup> sr cm <sup>-1</sup>
* UNCERTAINTY IN D	$\sigma_{\rm p}$ , = 1.69 × 10 <sup>11</sup>	$(molec/cm^2)(W/cm^2srcm^{-1})$









Table 18 Detection Parameters for  ${\rm N_20}$   $2\,{\rm v_1}$  band

QUANTITY	SYMBOL, VALUE	UNITS
DETECTION BAND	2525-2590	- l - cm
Approximate wavelength	4.0	Ę
* NO. OF SPECTRAL ELEMENTS (for $\Delta v$ = 0.10)	м = 650	
BAND PHOTON RADIANCE (scene)	1.04 × 10 <sup>14</sup>	ph/sec cm <sup>2</sup> sr
Maximum of contrast $\tau_{\nu}{}^{\alpha}{}_{g\nu}$	$CMAX = 3.51 \times 10^{-20}$	cm <sup>2</sup> /molec
Mean contrast	$\mu^* = 1.32 \times 10^{-20}$	cm <sup>2</sup> /molec
STANDARD DEVIATION OF CONTRAST	$a^2 = 8.95 \times 10^{-21}$	cm <sup>2</sup> /molec
* Photon flux density on detector		
* from scene	$2.4 \times 10^{12}$	phot/seccm <sup>2</sup>
* from internal sources	$2.5 \times 10^{12}$	phot/sec cm <sup>2</sup>
* T0TAL	$J = 4.9 \times 10^{12}$	phot/sec cm <sup>2</sup>
* BLIP D*	3.1 × 10 <sup>12</sup>	cm /HZ/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE mi	min t <sub>d</sub> = 1.63	sec
* CORRESPONDING BASELINE NESR	$(NESR)_0 = 5.4 \times 10^{-9}$	W/cm <sup>2</sup> sr cm <sup>-1</sup>
* MINIMUM DETECTABLE QUANTITY D (see figure) m	min $0 = 0.5 - 1.4 \times 10^{11}$	$(molec/cm^2)(W/cm^2 sr cm^{-1})$
* UNCERTAINTY IN D	$\sigma_{\rm D}$ = 1.9 × 10 <sup>10</sup>	$(molec/cm^2)(W/cm^2 srcm^{-1})$



 $N_2O v_3$  band





Table 19 Detection Parameters for  $N_20$   $v_3$  band

YTITANIO	SYMBOL, VALUE	UNITS
DETECTION BAND	2160-2210	cm - 1
Approximate wavelength	. 4.5	шn
* NO. OF SPECTRAL ELEMENTS (for $\Delta v$ = 0.10)	. M ≈ 500	6
BAND PHOTON RADIANCE (scene)	$2.23 \times 10^{14}$	ph/sec cm sr
Maximum of contrast togo	$CMAX = 8.93 \times 10^{-20}$	cm/molec 2/
Mean contrast	$\mu = 3.73 \times 10^{-3}$	cm /molec
STANDARD DEVIATION OF CONTRAST	. o' = 2.59 × 10 = .	
* Photon flux density on detector	;	c
* from scene	$5.1 \times 10^{12}$	phot/sec cm <sup>2</sup>
* from internal sources	$8.5 \times 10^{12}$	phot/sec cm <sup>2</sup>
* TOTAL	$0 = 1.4 \times 10^{15}$	phot/sec cm_
* BLIP D	. 2.2 × 10 <sup>12</sup>	cm /Hz/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE	min t <sub>d</sub> = 0.978	sec
* CORRESPONDING BASELINE NESR	$(NESR)_0 = 9.9 \times 10^{-9}$	W/cmf sr cm ' 2'21
* MINIMUM DETECTABLE QUANTITY D (see figure)	ITY D (see figure) $\dots$ min D = 0.3 - 1.0 × 10	(molec/cm ) (w/cm sr cm /
* UNCERTAINTY IN D	. 01 × 4.1 = 'Qp .	(molec/cm / w/cm st cm)



N<sub>2</sub>0 v, band






Table 20 Detection Parameters for  $N_2\theta - v_1$  band

QUANTITY	SYMBOL, VALUE	UNITS
DETECTION BAND	1250-1320	- l
Approximate wavelength	7.8	mı
* NO. OF SPECTRAL ELEMENTS (for $\Delta v$ = 0.10)	М = 700	
BAND PHOTON RADIANCE (scene)	6.62 × 10 <sup>15</sup>	ph/seccm <sup>2</sup> sr
Maximum of contrast $\tau_{\rm u}$ ชุง	$CMAX = 2.84 \times 10^{-20}$	cm <sup>2</sup> /molec
Mean contrast	$\mu^* = 3.40 \times 10^{-21}$	cm <sup>2</sup> /molec
STANDARD DEVIATION OF CONTRAST	$\sigma' = 5.50 \times 10^{-21}$	cm <sup>2</sup> /molec
* Photon flux density on detector		
* from scene	1.5 × 10 <sup>14</sup>	phot/sec cm <sup>2</sup>
* from internal sources	$3.1 \times 10^{14}$	phot/sec cm <sup>2</sup>
* TOTAL	$J = 4.6 \times 10^{14}$	phot/sec cm <sup>2</sup>
* BLIP D*	7.7 × 10 <sup>11</sup>	cm /Hz/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE m	min $t_d = 1.27 \times 10^{-2}$	Sec.
* CORRESPONDING BASELINE NESR	$(NESR)_0 = 2.5 \times 10^{-7}$	W/cm <sup>2</sup> sr cm <sup>-1</sup>
* MINIMUM DETECTABLE QUANTITY D (see figure)	min $D = 0.4 - 1.0 \times 10^{13}$	$(molec/cm^2)(W/cm^2 sr cm^{-1})$
* UNCERTAINTY IN D	$\sigma_{\rm D}$ = 2.1 × 10 <sup>12</sup>	$(molec/cm^2)(W/cm^2 sr cm^{-1})$
	•	









Table 21 Detection Parameters for NO  $_2$   $v_1 \pm v_3$  band

SY	SYMBOL, VALUE	UNITS
DETECTION BAND	2850-2935	cm 1
Approximate wavelength	3.44	wn
* NO. OF SPECTRAL ELEMENTS (for av = 0.10)	M = 850	
BAND PHOTON RADIANCE (scene)	3.41 × 10 <sup>13</sup>	ph/sec cm <sup>2</sup> sr
Maximum of contrast t, a,	$CMAX = 1.10 \times 10^{-19}$	cm <sup>2</sup> /molec
Ve an contrast.	$\mu^* = 2.28 \times 10^{-20}$	cm <sup>2</sup> /molec
10N OF COM	$a^2 = 1.99 \times 10^{-20}$	cm²/molec
* Photon flux density on detector		
* from scene	7.8 × 10 <sup>11</sup>	phot/sec cm
* from internal sources	8.5 × 10 <sup>11</sup>	phot/sec cm <sup>2</sup>
* T0TAL	$J = 1.6 \times 10^{12}$	phot/sec cm <sup>2</sup>
* BLIP 0	4.8 × 10 <sup>12</sup>	cm /Hz/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE min t <sub>d</sub> = 2.84	min t <sub>d</sub> = 2.84	sec
* CORRESPONDING BASELINE NESR $(\overline{\rm NESR})_0 = 2.7 \times 10^{-9}$ * MINIMUM DETECTABLE QUANTITY D (see figure) min D = 1.0 - 2.5 $\times$ $10^{10}$	$(NESR)_0 = 2.7 \times 10^{-9}$ min D = 1.0 - 2.5 × $10^{10}$	W/cm <sup>2</sup> sr cm   (molec/cm <sup>2</sup> ) (W/cm sr cm <sup>1</sup> )
* UNCERTAINTY IN D	$a_{D_1} = 4.3 \times 10^9$	(molec/cm <sup>2</sup> )(W/cm <sup>2</sup> sr cm <sup>-1</sup> )









Table 22 Detection Parameters for NO  $_2$   $\,\nu_2$  band

QUANTITY	SYMBOL, VALUE	UNITS
DETECTION BAND	710-795	- J
Approximate wavelength	13.3	<b>E</b> A
* NO. OF SPECTRAL ELEMENTS (for $\Delta v$ = 0.10)	M = 850	
BAND PHOTON RADIANCE (scene)	$5.32 \times 10^{17}$	ph/sec cm <sup>2</sup> sr
Maximum of contrast $ au_{\alpha}{}_{g_{V}}$	$CMAX = 1.03 \times 10^{-19}$	cm²/molec
Mean contrast	$\mu' = 2.95 \times 10^{-21}$	cm <sup>2</sup> /molec
STANDARD DEVIATION OF CONTRAST	$\sigma' = 6.58 \times 10^{-21}$	cm²/molec
* Photon flux density on detector		
* from scene	1.2 × 10 <sup>15</sup>	phot/sec cm <sup>2</sup>
* from internal sources	1.7 × 10 <sup>15</sup>	phot/sec cm <sup>2</sup>
* T0TAL	$J = 3.0 \times 10^{15}$	phot/sec cm <sup>2</sup>
* BLIP D*	5.16 × 10 <sup>11</sup>	cm /Hz/V
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE	min t <sub>d</sub> = 5.13 × 10 <sup>-3</sup>	Sec
* CORRESPONDING BASELINE NESR $(NESR)_0 = 5.9 \times 10^{-7}$	$(NESR)_0 = 5.9 \times 10^{-7}$	W/cm <sup>2</sup> sr cm <sup>-1</sup>
* MINIMUM DETECTABLE QUANTITY D (see figure) min D = 0.6-1.75 × 10 <sup>15</sup>	min $0 = 0.6 - 1.75 \times 10^{15}$	$(molec/cm^2)(W/cm^2 sr cm^{-1})$
* UNCERTAINTY IN D	$\sigma_{\mathbf{D}'} = 4.0 \times 10^{14}$	(molec/cm2)(W/cm2 sr cm-1)



 $so_2 - v_1 + v_3$  band





Table 23 Detection Parameters for  ${\rm SO}_2 - {\rm v_1} + {\rm v_3}$  band

QUANTITY	SYMBOL, VALUE	UNITS
DETECTION BAND	2450-2525	cm - 1
Approximate wavelength	0.4	wn
* NO. OF SPECTRAL ELEMENTS (for $\Delta v$ = 0.10)	M = 750	
BAND PHOTON RADIANCE (scene)	1.59 × 10 <sup>14</sup>	ph/sec cm <sup>2</sup> sr
Maximum of contrast $\tau_{\nu}{}^{\alpha}{}_{g\nu}$	$CMAX = 2.34 \times 10^{-20}$	cm <sup>2</sup> /molec
Mean contrast	$$ $\mu' = 7.82 \times 10^{-21}$	cm <sup>2</sup> /molec
STANDARD DEVIATION OF CONTRAST	$\sigma = 6.08 \times 10^{-21}$	cm <sup>2</sup> /molec
* Photon flux density on detector	1	
* from scene	$3.6 \times 10^{12}$	phot/sec cm <sup>2</sup>
* from internal sources	3.9 × 10 <sup>12</sup>	phot/sec cm <sup>2</sup>
* T0TAL	$3 = 7.5 \times 10^{12}$	phot/sec cm <sup>2</sup>
* BLIP D*	2.6 × 10 <sup>12</sup>	cm /Hz/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE	min t <sub>d</sub> = 1.32	sec
* CORRESPONDING BASELINE NESR	$\dots \dots (NESR)_0 = 7.2 \times 10^{-9}$	W/cm <sup>2</sup> sr cm <sup>-1</sup>
* MINIMUM DETECTABLE QUANTITY D (see figure) $\kappa$ in D = 0.9 - 2.5 $ imes$ 10 $^{11}$	min D = 0.9-2.5 x 10 <sup>11</sup>	(molec/cm <sup>2</sup> ) (W/cm <sup>2</sup> sr cm <sup>-1</sup> )
* UNCERTAINTY IN D	$\sigma_{\rm D} = 3.8 \times 10^{10}$	(molec/cm <sup>2</sup> )(W/cm <sup>2</sup> sr cm <sup>-1</sup> )








Table 24 Detection Parameters for  $\mathrm{SO}_2$   $\,\,\mathrm{v}_1$  band

QUANTITY	SYMBOL, VALUE	UNITS
DETECTION BAND	1090-1210	- 1 Cm
Approximate wavelength	8.7	En
* NO. OF SPECTRAL ELEMENTS (for $\Delta v$ = 0.10)	M = 1200	
BAND PHOTON RADIANCE (scene)	3.18 × 10 <sup>16</sup>	ph/sec cm <sup>2</sup> sr
Maximum of contrast $\tau_{\nu}\alpha_{q\nu}$ CMA	$CMAX = 5.13 \times 10^{-20}$	cm <sup>2</sup> /molec
•	$\mu^* = 1.30 \times 10^{-20}$	cm <sup>2</sup> /molec
STANDARD DEVIATION OF CONTRAST	$\sigma' = 9.61 \times 10^{-21}$	cm <sup>2</sup> /molec
* Photon flux density on detector		
* from scene	7.3 × 10 <sup>14</sup>	phot/sec cm <sup>2</sup>
* from internal sources	$8.2 \times 10^{14}$	phot/sec cm <sup>2</sup>
* TOTAL	J = 1.5 × 10 <sup>15</sup>	phot/sec cm <sup>2</sup>
* BLIP DAC	4.7 × 10 <sup>11</sup>	cm /Hz/W
* MINIMUM SCAN TIME FOR BLIP PERFORMANCE min t	min $t_d = 7.07 \times 10^{-3}$	sec
* CORRESPONDING BASELINE NESR	$(NESR)_0 = 5.5 \times 10^{-7}$	W/cm <sup>2</sup> sr cm <sup>-1</sup>
* MINIMUM DETECTABLE QUANTITY D (see figure) min D = $0.3 - 1.0 \times 10^{13}$	$0 = 0.3 - 1.0 \times 10^{13}$	$(molec/cm^2)(W/cm^2 sr cm^{-1})$
# O N   A   N   O N   A   N   O N	$\frac{1}{2}$ = 1 $\frac{1}{4}$ $\frac{1}{2}$	(m) 100 /cm <sup>2</sup> ) (11/cm <sup>2</sup> er cm <sup>-1</sup> )

